## 30,000 Mile or 24 Month Maintenance: 00-05

Procedure Performed (check off or initial)	30,000 Mile (48 270 km) or 24 Month Maintenance*	МОР
Inspect	Engine Drive Belt Inspecting	01–01
Check	Engine-Support Fasteners Checking	01–02
Change	Engine Oil and Filter (see the engine manufacturer's manual)	_
Change	Air Cleaner Replacement	09–01
Inspect	Charge Air Cooler (CAC) Inspection and Cleaning (if cleaning is needed)	09–02
Inspect	Air Compressor Inspection	13–01
Check	Alternator, Battery, and Starter Connections Check	15–01
Inspect/ Check	Radiator (radiator cap, coolant freeze points, SCA levels, hose routing for chaffing and leaks)	20–01, 20–02, 20–03
Change	Mechanical Fan Drive Gearbox Oil Change	20-04
Lubricate	Mechanical Fan Drive Gearbox Lubrication	20–05
Change	Transmission Fluid and Filter (if required by Allison)	26–03
Inspect	Transmission Hose Routing for Chaffing and Leaks	_
Lubricate	Throttle Pedal Pivot Pin Lubricating	30–01
Check	Suspension Fastener Torque Check	32–01
Check	Suspension Height Control Valve Check	32–02
Lubricate	ZF IFS Lubrication	32–04
Check	Suspension U-Bolt Torque Check	32–06
Inspection	V-Ride Rear Suspension Inspection	32–07
Lubricate	Knuckle Pin Lubricating <sup>†</sup>	33–01
Lubricate	Tie-Rod End Lubricating and Inspecting <sup>†</sup>	33–02
Inspect	Wheel End Inspecting	33–04
Check/ Change	Oil-Filled Hubs Oil Changing (front and tag axle)	33–05, 33–06, 35–04, 35–05
Check	Axle Seals for Leaks	_
Change	Axle Lubricant Changing and Magnetic Plug Cleaning (Detroit and Meritor axles)	35–02
Check	Axle Breather Checking	35–03
Check	Wheel Nut Checking	40–01
Check	Tire Pressure	_
Lubricate	Driveline Inspection and Lubrication	41–01
Inspect	Brake System Valves Inspecting	42-01

## 30,000 Mile or 24 Month Maintenance: 00-05

Procedure Performed (check off or initial)	30,000 Mile (48 270 km) or 24 Month Maintenance*	МОР
Inspect	Air Dryer and Air Lines for Proper Routing, Chaffing, and Leaks	42-02
Lubricate	Camshaft Bracket Bushing Lubricating	42–04
Lubricate	Slack Adjuster Lubricating	42–05
Lubricate	Foot Brake Valve Actuator Lubricating	42–06
Inspect	Bendix Hydro-Max® Brake System Inspecting (front-engine only)	42-07
Lubricate	Brake Caliper Slide Pin Lubricating, Bosch Brakes (front- engine diesel chassis)	42-08
Check	Brake Lines Checking, Hydraulic Disc or Air Brakes	42-09
Check	Brake Lining Wear Checking, Hydraulic Disc Brakes (front-engine only)	42–10
Inspect	Brake Inspecting (air brakes)	42–11
Lubricate	Meritor Roller Pin Lubricating	42–12
Drain	Air Tanks	
Lubricate	Drag Link Lubricating	46–01
Change	Power Steering Fluid and Filter Changing	46–03
Lubricate	Steering Driveline Lubricating	46–04
Lubricate	Steering Gear Lubricating	46–05
Change	Hydraulic Reservoir Filter Changing (including TRW)	46–06
Inspect	Fuel Tank Mounts and Fuel Line Checking	47–01
Change	Fuel Filters	_
Inspect	Exhaust System Inspecting	49–01
Check	Ground Cables Checking and Cleaning	54–01
Inspect	Air Conditioner Component Inspection	83–01
Customer <sup>‡</sup> Date		

<sup>\*</sup> Additional copies are available on the Freightliner Custom Chassis Corporation website (www.freightlinerchassis.com).

<sup>&</sup>lt;sup>†</sup> For vehicles with Detroit axles, complete this procedure once a year or every 25,000 miles (40 000 km), whichever comes first

<sup>&</sup>lt;sup>‡</sup> Your signature on this form indicates that you have reviewed and agree to the service items to be performed. Any items you wish to exclude should be indicated with a "no" to the left of that service item.